(F)

OFFICE OF NAVAL RESEARCH

Contract N00014-88-AF-00001

R&T Code 413d001---03

TECHNICAL REPORT NO. 31

NMR, DSC, and Electrical Conductivity Studies  ${\rm of\ MEEP\ Complexed\ with\ NaCF_3SO_3.}$ 

by

John J. Fontanella & Mary C. Wintersgill

Prepared for Publication

in

Solid State Ionics

U. S. Naval Academy Department of Physics Annapolis, MD 21402-5026 SELECTE DELLIS,1988

June 1988

Reproduction in whole or in part is permitted for any purpose of the United States Government

This document has been approved for public release and sale; its distribution is unlimited

·····						
		REPORT DOCUM	MENTATION	PAGE		
1a, REPORT SECURITY CLASSIFICATION  Unclassified			16 RESTRICTIVE MARKINGS			
28. SECURITY CLASSIFICATION AUTHORITY			L	/AVAILABILITY OF		
2b. DECLASSIFICATION / DOWNGRADING SCHEDULE				ent has been I sale: its o		
	*****		release and sale; its distribution is unlimited.			
4. PERFORMING ORGANIZATION REP	ORT NUMBE	R(S)	5. MONITORING	ORGANIZATION RE	PORT NUMBER	S)
31						
6a. NAME OF PERFORMING ORGANIZ	ZATION	6b. OFFICE SYMBOL (If applicable)	7a. NAME OF MONITORING ORGANIZATION			
U. S. Naval Academy			,			
6c. ADDRESS (City, State, and ZIP Coo	ie)	· · · · · · · · · · · · · · · · · · ·	76. ADDRESS (Cit	ry, State, and ZIP (	ode)	
Physics Department						
Annapolis, MD 21402-50	026					
8a. NAME OF FUNDING/SPONSORING ORGANIZATION	3	8b. OFFICE SYMBOL (If applicable)	9. PROCUREMEN	T INSTRUMENT IDE	NTIFICATION NU	JMBER
Office of Naval Research	ch	ONR				
8c. ADDRESS (City, State, and ZIP Cod	e)		10 SOURCE OF	FUNDING NUMBER	s	<del></del>
800 N. Quincy Street	200		PROGRAM ELEMENT NO.	PROJECT NO.	TASK NO.	WORK UNIT
Arlington, VA 22217-50	J00		61153Ñ	RR013-06-0C	1	ACCESSION NO
11. TITLE (Include Security Classificat	ion)		1 011331	KK013-00-00	027-793	_1
NMR, DSC, and Electr (Unclassified)	ical Cor	nductivity Studi	es of MEEP C	Complexed wit	h NaCF3SO3	
12. PERSONAL AUTHOR(S)	h- 1 E	antanalla and Ma	m. C. Wanton	:11		
	13b. TIME C	ontanella and Ma	<u> </u>			
Interim		/10/1 TO88/9/30	June 1	ORT (Year, Month, L 988	15. PAGE	
16. SUPPLEMENTARY NOTATION				/		
				/		/
17 COSATI CODES			Continue on reverse if necessary and identify by block number)			
FIELD GROUP SUB	-GROUP	Prepared fo	or publication in Solid State Ionics, (mgm)			
		1	•	phos	phazene	3.
19. ABSTRACT (Continue on Everse	if necessary	and identify by block of	umber)			
23Na N	MR, electric	al conductivity, and DSC	studies have been	carried out on ME	EP	;
complexed with	NaCF3SO3.	. All results are similar to	those for other am	orphous ion conduct	ting	/
polymers. Spe	cifically, the	NMR spectrum associate	d with mobile Na	ions exhibits motio	nai	/
i e		ansition temperature, and a	_	· n	,	/
linewidth meas	urements refl	ect localized motion of the	cations. The electric	cal conductivity exhi	bits	
the usual non-	Arrhenius be	havior. However, using p	revious data for PD	MS-EO complexes,	it is	
shown that the	VTF or WL	F equations are only appro	eximate as the parac	neters depend upon	the	<b>/</b> .
temperature ra	nge. This sh	eds light on several discre	pancies in the liter	ature.		
20 DISTRIBUTION / AVAILABILITY OF	ABSTRACT	RPT DITIC USERS	21 ABSTRACT SE	CURITY CLASSIFICA	TION Unc 1	assified
224 NAME OF RESPONSIBLE INDIVID	201-24	(Include Area Code) 57–3487				
	JUIII U.	Fontanella	4 301-20	11-2401	1	

# NMR, DSC, AND ELECTRICAL CONDUCTIVITY STUDIES OF MEEP COMPLEXED WITH NaCF3SO3

S. G. Greenbaum, K. J. Adamic, Y. S. Pak

Physics Department, Hunter College of CUNY, New York, NY 10021

M. C. Wintersgill, J. J. Fontanella

Physics Department, U.S. Naval Academy, Annapolis, MD 21402

# **ABSTRACT**

23Na NMR, electrical conductivity, and DSC studies have been carried out on MEEP complexed with NaCF<sub>3</sub>SO<sub>3</sub>. All results are similar to those for other amorphous ion conducting polymers. Specifically, the NMR spectrum associated with mobile Na<sup>+</sup> ions exhibits motional narrowing above the glass transition temperature, and activation energies deduced from both T<sub>1</sub> and linewidth measurements reflect localized motion of the cations. The electrical conductivity exhibits the usual non-Arrhenius behavior. However, using previous data for PDMS-EO complexes, it is shown that the VTF or WLF equations are only approximate as the parameters depend upon the temperature range. This sheds light on several discrepancies in the literature.

		•
Access	ion For	_
NTIS DTIC T Unanno Justif	AB 🗓	DTIC COPY INSPECTED
By	ibution/	
Avai	lability Codes	
Dist	Avail and/or Special	
A-I		

STANDARD FOR THE PROPERTY OF T

#### 1. Introduction

In recent papers, the authors have reported nuclear magnetic resonance (NMR), electrical conductivity, and differential scanning calorimetry studies (DSC) on poly(propylene oxide) (PPO) [1,2] and poly(dimethylsiloxane-ethylene oxide) (PDMS EO) [3,4] complexed with sodium salts. In the present note, the work is extended to poly(bis-methoxyethoxyethoxide) phosphazene (MEEP) complexed with alkali metal salts. The motivation for the work is that MEEP exhibits a rather high ionic conductivity at room temperature [5-7] and thus is of interest as a solid electrolyte.

### 2. Experiment and Data Reduction

The MEEP was dried in vacuum for 48 hours at 110°C prior to use. It was dissolved in tetrahydrofuran in a teflon cup and sodium triflate was added while stirring. The concentration was one sodium ion per four polymer repeat units. For the electrical measurements the sample was loaded into a shielded cavity which was then attached to the cold finger of a Precision Cryogenics CT-14 dewar. All procedures, including loading of the DSC pans and NMR sample tube were carried out in a dry box with a relative humidity of less than 5%.

All remaining techniques is making the electrical, NMR, and DSC measurements are the same as described elsewhere [3]. In the case of the electrical conductivity, a different data analysis technique was applied since the cell did not lend itself well to geometric data reduction. Instead, the dielectric constant at 77K was set equal to 5 with subsequent scaling of the imaginary part of the dielectric constant and ultimately the electrical conductivity. Consequently, there is some uncertainty associated with the absolute value of the electrical conductivity. However, the precision of the data is quite good, probably better than 1%, and since the results are only uncertain by some multiplicative factor, the values of T<sub>0</sub> and E<sub>a</sub> determined as described below remain reliable.

# 3. Results and Discussion

#### 3.1. DSC

The results of the DSC measurements are shown in fig. 1. For the uncomplexed MEEP the onset, central, and end of the glass transition occur at -82, -78, and -73°C, respectively. As expected, the corresponding values for MEEP<sub>4</sub>:NaCF<sub>3</sub>SO<sub>3</sub> are higher, -61, -54, and -47°C, respectively. The increase in the glass transition temperature in PPO, for example, with the addition of salt is a well known phenomenon [8].

#### 3.2. NMR

The  $^{23}$ Na NMR results are qualitatively similar to those obtained for a variety of amorphous polymer - sodium salt complexes. [1-4] As in the other materials two distinct spectral responses were observed, one associated with mobile Na<sup>+</sup> and the other with a bound Na configuration. The mobile resonance is characterized by spin lattice relaxation times (T<sub>1</sub>) that are typically two or three orders of magnitude shorter than the bound resonance T<sub>1</sub>. Only small quantities (less than  $\sim$  5%) of the nuclei giving rise to the total signal could be identified with the bound Na at any given temperature throughout the range of measurement (133-371K). Thus no attempt was made to determine the relative concentrations of bound and mobile Na as a function of temperature, as had previously been done for PDMS/EO [3] and PPO [2] complexes.

Figure 2 is an Arrhenius plot of  $T_1$ , for the mobile Na resonance obtained at an operating frequency of 81 MHz. The relatively small  $T_1$  values (<10 ms) which occur even below  $T_g$  suggest the presence of short range ion motion. These motions may be associated with hopping within a frozen lattice, [9] although it is well recognized that the rate determining process for ionic conductivity involves segmental motion of the polymer above  $T_g$ . The presence of a  $T_1$  minimum is the vicinity of 318 K is clear from the data, and the roughly linear region between 213 and 306 K indicates an activation energy of approximately 0.27eV. Similar  $T_1$  behavior has been observed in a PDMS/EO - NaCF<sub>3</sub> COO complex [4].

Figure 3 represents an Arrhenius plot of  $(T_2^*)^{-1}$ , the reciprocal of the free induction decay constant, where (  $\sim T_2^*)^{-1}$  is approximately equal to the full-width-at-half-maximum linewidth. As observed in all other sodium salt-polymer complexes studied in this laboratory, [1-4] the <sup>23</sup>Na resonance (associated with the mobile cation) begins to narrow just above the central T<sub>g</sub>. The linear region between 223 and 268 K implies an activation energy of about 0.20eV. The activation energies inferred from the T<sub>1</sub> and T<sub>2</sub>\* data are considerably smaller (by nearly an order of magnitude) than the value that would be obtained in attempting to fit the conductivity to an Arrhenius relationship by neglecting the curvature of the data points. Again this indicates that local motions are primarily responsible for both spin-lattice relaxation and resonance line narrowing. The T<sub>1</sub> mechanism is most probably mediated by the interaction between the <sup>23</sup>Na quadrupole moment and fluctuations of the surrounding electric field gradient whereas T2\* is influenced by both the quadrupole interaction and dipolar interactions, as it has been observed that the spin-spin relaxation time, T2 (determined from spin-echo measurements) also exhibits an increase in the region of the motional narrowing. From the data in Figure 3, it can be seen that the resonance begins to broaden above 278K. This is apparently a result of lifetime broadening as T<sub>1</sub> reaches values of only several hundred microseconds in this temperature region.

## 3.3. Electrical Conductivity

The results of the electrical conductivity studies for the complexed material are shown in fig. 4. The electrical conductivity for the uncomplexed MEEP was too low to be measured in the cell used in the present work. The curvature which is often observed for non-crystalline ion containing polymers is apparent. Consequently, the VTF equation [10] in the form:

$$\sigma = AT^{-1/2} \exp\{-E_a/k(T-T_0)\}$$
 (1)

was best-fit to the data using techniques described in detail elsewhere [4]. The values of the fitting parameters were determined to be Ea=0.0848 eV (8.18 kJ/mol),  $T_0=175.3$  K, and  $log_{10}A=+0.25$  and the RMS deviation in  $log_{10}\sigma$  was 0.049.

The strong curvature resolves one point concerning MEEP. Namely, previous workers [6,7] were unable to distinguish between Arrhenius and VTF behavior though shallow curvature was reported. The reason, of course, is that those authors did not extend their work to low enough temperatures as they were confined to the region above 270K. The present work makes it clear that MEEP exhibits VTF behavior as do other amorphous polymers such as PPO [1,2,10,11] or PDMS-EO [3,4,12].

Further, the value of  $T_0$  is found to be 44°C below the "central"  $T_g$  as determined by DSC. This is similar to previous results for PPO [1,2] and PDMS-EO [3,4] obtained by the authors. The present value of  $T_0$  is somewhat higher than the values of Tonge and Shriver [7] who fit both eq. (1) and an Arrhenius expression to their data. Those authors find values of  $T_g$ - $T_0$  from 50 to 120K. (The values of  $T_g$  quoted by Tonge and Shriver are several degrees lower than the "central"  $T_g$ 's of the present work and thus the values to be compared with 44K of the present work are probably about 60-120K.)

This discrepancy can be explained at least in part by the difference in temperature range between the two experiments. To show this, the data from ref. 4 has been reanalyzed using eq. (1) over various temperature ranges. The data of the present work were not used because of the limited temperature range involved. The comparison is probably quite good because the  $T_0$ 's are similar, being 175K in the present work for MEEP and 176K for PDMS-EO [4]. The results are listed in Table 1. It is seen that when the data below 300K are eliminated, the values of  $T_0$  begin to decrease rapidly along with a corresponding increase in  $E_a$ . Consequently, data whose range begins far above  $T_g$  are expected to exhibit a low value of  $T_0$  as is the case for the results of Tonge and Shriver.

This, of course, points out the approximate nature of the VTF equation. Specifically, it shows that the data is more Arrhenius at high temperatures than is allowed by the VTF equation.

A similar observation has been reported recently by Giles [14] for amorphous phosphate ester extended and crosslinked poly(ethylene glycol) complexed with LiCF3SO3.

It is also apparent from Table 1 that if only a few of the lowest temperature data points are eliminated, the values of  $T_0$  are higher than expected. This accounts, at least in part, for a previously noted discrepancy in comparing our results for PDMS-EO [3,4] with those of Bouridah et. al. [13]. Specifically,  $T_0$  is lower and  $E_a$  is larger than those parameters reported by the latter group, whose data began at about 295K.

It is of interest to investigate this effect more closely. Both low and high temperature data from ref. 4 were eliminated and eq. (1) was best fit to the data. Those results are also listed in Table 1. A very strong increase in the value of  $T_0$  is accompanied by a strong decrease in  $E_a$ . Consequently, this shows that intermediate temperature range data will exhibit large values of  $T_0$  and small values of  $E_a$ .

It is important to note that this effect causes  $E_a$  to always decrease when  $T_0$  increases. Consequently, this behavior cannot account for the variation of  $T_0$  and  $E_a$  with pressure, for example, which has recently been reported [12]. The reason is that it was found that both  $E_a$  and  $T_0$  increase as pressure increases [12]. Of course, as eq. (1) was fit to the data over different temperature ranges, the actual values will be affected somewhat.

In order to further emphasize the approximate nature of the VTF or WLF equations, it is pointed out that Nozaki and Mashimo have recently reported very low frequency dielectric relaxation data in poly(vinyl acetate) and showed that the relaxation time exhibits Arrhenius behavior below  $T_g$  [15]. This is consistent with the recent comments of Giles [14].

Finally, for completeness, the VTF equation in the form:

$$\sigma = A' \exp\{-E_a'/k(T-T_o')\}$$
 (2)

was best-fit to the data and the resulting fitting parameters were  $\log_{10}A' = -1.09$ ,  $E_a' = 0.082$  eV, and  $T_o' = 176.3$  K. In addition, the mathematically equivalent WLF equation [16]

$$\log_{10}(\sigma(T)/\sigma(T_g)) = C_1(T-T_g)/(C_2+T-T_g)$$
 (3)

was best-fit to the data with the resultant fitting parameters given in Table 2. The WLF parameters are similar to those reported for other amorphous materials [1,3,4,12].

#### **ACKNOWLEDGMENTS**

The authors would like to thank T. Nishikawa of Shin Nisso Kako, Tokyo, Japan for providing the MEEP sample. Mr. A. Howard is acknowledged for assistance with the NMR measurements. This work was supported in part by the Office of Naval Research, and the PSC CUNY Research Award Program.

#### REFERENCES

- [1] S. G. Greenbaum, Y. S. Pak, M. C. Wintersgill, J. J. Fontanella, J. W. Schultz, and C. G. Andeen, J. Electrochem. Soc., to be published.
- [2] M. C. Wintersgill, J. J. Fontanella, S. G. Greenbaum, and K. J. Adamic, British Polymer J., to be published.
- [3] M. C. Wintersgill, J. J. Fontanella, M. K. Smith, S. G. Greenbaum, K. J. Adamic, and C. G. Andeen, Polymer 28 (1987) 633.
- [4] K. J. Adamic, S. G. Greenbaum, M. C. Wintersgill, and J. J. Fontanella, J. Appl. Phys. 60 (1986) 1342.
- [5] P. M. Blonsky, D. F. Shriver, P. Austin, and H. R. Allcock, J. Am. Chem. Soc. 106 (1984) 6854.
- [6] P. M. Blonsky, D. F. Shriver, P. Austin, and H. R. Allcock, Solid St. Ionics 18&19 (1986) 258.
- [7] J. S. Tonge and D. F. Shriver, J. Electrochem. Soc. 134 (1987) 269.
- [8] A. Eisenberg and M. King, Ion-Containing Polymers, Academic, New York, 1977, pp. 45-48.
- [9] M.A. Ratner, in <u>Polymer Electrolyte Reviews</u>, ed. J.R. Mac Callum and C. A. Vincent, Elsevier Applied Science, London, 1987, p.173.
- [10] H. Vogel, Physik Z. 22 (1921) 645; V. G. Tammann and W. Hesse, A. Anorg. Allg. Chem. 156(1926) 245; G. S. Fulcher, J. Am. Ceram. Soc. 8 (1925) 339.
- [11] M. B. Armand, J. M. Chabagno, and M. J. Duclot, in <u>Fast Ion Transport in Solids</u>, ed. P. Vashishta, J. N. Mundy, and G. K. Shenoy, North Holland, New York, 1979, p. 131.
- [12] J. J. Fontanella, M. C. Wintersgill, M. K. Smith, J. Semancik and C. G. Andeen, J. Appl. Phys. 60 (1986) 2665.

- [13] A. Bouridah, F. Dalard, D. Deroo, H. Cheradame, and J. F. Le Nest, Solid State Ionics 15 (1985) 233.
- [14] J. R. M. Giles, Solid St. Ionics 24 (1987) 155.
- [15] R. Nozaki and S. Mashimo, J. Chem. Phys. 87 (1987) 2271.
- [16] M. L. Williams, R. F. Landel, and J. D. Ferry, J. Am. Chem. Soc. 77 (1955) 3701.

Table 1. Best fit VTF parameters for PDMS-EO using the data of ref. 4.

Temperature Range	log <sub>10</sub> A (Ω-cm) 1 K1	/2 <sup>E</sup> a <sup>(eV)</sup>	T <sub>O</sub> (K)	RMS Deviation	
250-380 260-380 270-380 280-380 290-380 300-380 310-380 320-380 250-340 255-340 260-340 270-340 275-340 280-340 280-340 290-340 290-340 305-340 305-340 310-340 315-340	-0.50 -0.57 -0.61 -0.62 -0.66 -0.64 -0.54 -0.23 -0.37 -0.42 -0.48 -0.53 -0.52 -0.56 -0.51 -0.64 -0.65 -0.71 -0.79 -0.90 -0.99	0.103 0.099 0.097 0.097 0.094 0.095 0.102 0.125 0.108 0.106 0.103 0.101 0.101 0.099 0.102 0.095 0.094 0.091 0.087 0.081 0.076 0.067	176.4 178.9 180.2 180.7 182.4 181.8 176.1 157.7 173.9 175.3 176.8 178.3 176.8 179.4 177.5 182.1 182.7 184.8 188.4 192.7 196.5 204.5	0.0096 0.0069 0.0063 0.0062 0.0060 0.0064 0.0057 0.0056 0.0046 0.0039 0.0040 0.0038 0.0017 0.0018 0.0018 0.0013 0.0010 0.0009 0.0003	
				_	

Table 2. DSC results and best fit WLF parameters for  ${\rm MEEP}_4{\rm NaCF}_3{\rm SO}_3$ .

	T <sub>g</sub> (K)	c <sub>1</sub>	c <sub>2</sub> (K)	$\log_{10}\sigma(T_g)(\Omega-cm)^{-1}$	RMS Deviation
Onset	212	11.5	35.7	-12.6	0.048
Central	219	9.6	42.7	-10.7	0.048
End	226	8.3	49.7	-9.4	0.048




Figure 1. DSC themogram for (a) uncomplexed MEEP-solid line and (b) MEEP $_4$ NaCF $_3$ SO $_3$ -dotted line. The data were taken at 10 K/min.




Figure 2. Arrhenius plot of the  $^{23}$ Na spin-lattice relaxation time in MEEP $_4$ NaCF $_3$ SO $_3$ . The spectrometer frequency is 81 MHz and the T $_1$  minimum occurs at about 318K.




Figure 3. Arrhenius plot of the inverse  $^{23}$ Na free induction decay constant,  $(T_2^*)^{-1}$ , in MEEP<sub>4</sub>NaCF<sub>3</sub>SO<sub>3</sub>.




Figure 4. Arrhenius plot of the electrical conductivity data for  ${\tt MEEP_4NaCF_3SO_3}. \ \ {\tt The solid line is the best fit VTF equation (eq. 1)}.$ 

# TECHNICAL REPORT DISTRIBUTION LIST, GEN

	No. Copies	·	No. Copies
Office of Naval Research Attn: Code 1113 800 N. Quincy Street Arlington, Virginia 22217-5000	2	Dr. David Young Code 334 NORDA NSTL, Mississippi 39529	1
Dr. Bernard Douda Naval Weapons Support Center Code 50C Crane, Indiana 47522-5050	1	Naval Weapons Center Attn: Dr. Ron Atkins Chemistry Division China Lake, California 93555	1
Naval Civil Engineering Laboratory Attn: Dr. R. W. Drisko, Code L52 Port Hueneme, California 93401	1	Scientific Advisor Commandant of the Marine Corps Code RD-1 Washington, D.C. 20380	1
Defense Technical Information Center Building 5, Cameron Station Alexandria, Virginia 22314	12 high quality	U.S. Army Research Office Attn: CRD-AA-IP P.O. Box 12211 Research Triangle Park, NC 27709	1
DTNSRDC Attn: Dr. H. Singerman Applied Chemistry Division Annapolis, Maryland 21401	1	Mr. John Boyle Materials Branch Naval Ship Engineering Center Philadelphia, Pennsylvania 1911	1
Dr. William Tolles Superintendent Chemistry Division, Code 6100 Naval Research Laboratory Washington, D.C. 20375-5000	1	Naval Ocean Systems Center Attn: Dr. S. Yamamoto Marine Sciences Division San Diego, California 91232	1